



## TP-Link Archer NX600 draadloze router Gigabit Ethernet Dual-band (2.4 GHz / 5 GHz) 5G Wit

**Merk :** TP-Link

**Productfamilie:** Archer

**Artikelcode:** ARCHER NX600

**Productnaam :** Archer NX600

TP-Link Archer NX600. Type WAN-aansluiting: RJ-45. Wifi-band: Dual-band (2.4 GHz / 5 GHz), Wifi-standaard: Wi-Fi 6 (802.11ax), Wi-Fi-standaarden: 802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac), Wi-Fi 6 (802.11ax). Interfacetype Ethernet LAN: Gigabit Ethernet, Ethernet LAN, data-overdrachtsnelheden: 10,100,1000,2500 Mbit/s, Maximaal Tx-vermogen (2,4 GHz): 20 dBmW. Generatie mobiel internet: 5G, 3G standaarden: DC-HSDPA, HSPA, HSPA+, UMTS, 4G standaard: LTE-TDD & LTE-FDD. Ondersteunde beveiligingsalgoritmen: 64-bit WEP, 128-bit WEP, WPA, WPA-PSK, WPA2, WPA2-PSK



WAN-verbinding		Beveiliging	
Ethernet WAN *	✓	URL- filtering	✓
DSL WAN *	✗	DMZ support	✓
SIM-kaartsleuf *	✓	<b>Protocollen</b>	
Type WAN-aansluiting	RJ-45	DHCP client	✓
<b>Draadloos LAN</b>		DHCP server	✓
Wifi-band *	Dual-band (2.4 GHz / 5 GHz)	Universal Plug and Play ( UPnP )	✓
Wifi-standaard *	Wi-Fi 6 (802.11ax)	Ondersteunde netwerkprotocollen	IPv4, IPv6
Wi-Fi-standaarden	802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac), Wi-Fi 6 (802.11ax)	<b>Design</b>	
<b>Netwerk</b>		Kleur van het product	Wit
Ethernet LAN *	✓	<b>Certificaten</b>	
Interfacetype Ethernet LAN *	Gigabit Ethernet	Certificaten van naleving	CE, RoHS
Ethernet LAN, data-overdrachtsnelheden	10,100,1000,2500 Mbit/s	<b>Inhoud van de verpakking</b>	
Port forwarding	✓	Meegeleverde kabels	LAN (RJ-45)
Poortactivering	✓	Inclusief AC-adapter	✓
Dynamic DNS (DDNS)	✓	Snelle installatiehandleiding	✓
Aantal gastnetwerken (2.4 GHz)	1	<b>Antenne</b>	
Aantal gastnetwerken (5 GHz)	1	Antenne-ontwerp *	Intern & extern
Maximaal Tx-vermogen (2,4 GHz)	20 dBmW	Aansluiting antenne	SMA
Maximaal Tx-vermogen (5 GHz)	30 dBmW	Antennas quantity	14

Mobiel netwerken		Energie	
Generatie mobiel internet	5G	AC-ingangsspanning	100 - 240 V
3G standaarden	DC-HSDPA, HSPA, HSPA+, UMTS	AC-ingangsfrequentie	50/60 Hz
4G standaard	LTE-TDD & LTE-FDD	Spanning	12 V
5G-banden ondersteund	700,800,850,900,1800,2100,2300,2500,2600,3500,3700 MHz	Output current	2 A
4G frequentie ondersteund	700,800,850,900,1800,2100,2300,2500,2600,3500,3700 MHz	<b>Eisen aan de omgeving</b>	
3G bands ondersteund	850,900,2100 MHz	Bedrijfstemperatuur (T-T)	0 - 40 °C
SIM card type	NanoSIM	Temperatuur bij opslag	-40 - 70 °C
<b>Beheerfuncties</b>		Relatieve vochtigheid in bedrijf (V-V)	10 - 90 procent
Wifi Multimedia (WMM)/(WME)	✓	Luchtvochtigheid bij opslag	5 - 90 procent
Quality of Service (QoS)	✓	<b>Minimale systeemeisen</b>	
Reset button	✓	Windows 10, Windows 10 Education, Windows 10 Education x64, Windows 10 Enterprise, Windows 10 Enterprise x64, Windows 10 Home, Windows 10 Home x64, Windows 10 IoT Core, Windows 10 IoT Enterprise, Windows 10 Pro, Windows 10 Pro x64, Windows 2000, Windows 2000 Professional, Windows 7, Windows 7 Enterprise, Windows 7 Enterprise x64, Windows 7 Home Basic, Windows 7 Home Basic x64, Windows 7 Home Premium, Windows 7 Home Premium x64, Windows 7 Professional, Windows 7 Professional x64, Windows 7 Starter, Windows 7 Starter x64, Windows 7 Ultimate, Windows 7 Ultimate x64, Windows 7 x64, Windows 8, Windows 8 Enterprise, Windows 8 Enterprise x64, Windows 8 Pro, Windows 8 Pro x64, Windows 8 x64, Windows 8.1, Windows 8.1 Enterprise, Windows 8.1 Enterprise x64, Windows 8.1 Pro, Windows 8.1 Pro x64, Windows 8.1 x64, Windows 98SE, Windows NT, Windows RT 8.1, Windows Vista, Windows Vista Business, Windows Vista Business x64, Windows Vista Enterprise, Windows Vista Enterprise x64, Windows Vista Home Basic, Windows Vista Home Basic x64, Windows Vista Home Premium, Windows Vista Home Premium x64, Windows Vista Ultimate, Windows Vista Ultimate x64, Windows XP, Windows XP Home, Windows XP Home x64, Windows XP Professional, Windows XP Professional x64	
WPS Push Button Security	✓	Ondersteunt Windows	
<b>Beveiliging</b>		Ondersteunt Linux	✓
Ondersteunde beveiligingsalgoritmen	64-bit WEP, 128-bit WEP, WPA, WPA-PSK, WPA2, WPA2-PSK	Ondersteunt Mac-besturingssysteem	✓
Toegang voor gasten	✓	Mac-compatibiliteit	✓
DoS aanval preventie	✓	<b>Gewicht en omvang</b>	
Ouderlijk toezicht	✓	Breedte	99 mm
Filtratie	✓	Diepte	99 mm
IP-adresfilter	✓	Hoogte	190 mm



8885020624878

### Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.