



LevelOne SFP-3001 netwerk transceiver module Vezel-optiek 1250 Mbit/s 850 nm

Merk : LevelOne

Artikelcode: SFP-3001

Productnaam : SFP-3001



SFP-3001

LevelOne SFP-3001 netwerk transceiver module Vezel-optiek 1250 Mbit/s 850 nm:

850nm VCSEL

Data Rate: 1.25Gbps

Single +3.3V Power Supply

RoHS Compliant and Lead-free

AC/AC Differential Electrical Interface

Compliant with Multi-Source Agreement(MSA)

Duplex LC Connector

Compliance with specifications for IEEE 802.3z Gigabit Ethernet at 1.25Gbps

Compliance with ANSI specifications for Fiber Channel applications at 1.06Gbps

No configuration or installation software required

Eye Safety Designed to meet LASER Class 1 comply with EN60825-1

LevelOne SFP-3001. SFP transceiver type: Vezel-optiek, Maximale overdrachtssnelheid van gegevens:

1250 Mbit/s, Soort aansluiting: SFP. Ingangsspanning: 3.3 V, Maximaal voltage: 6 V, Stroom (max.): 0,3

A. Certificaten van naleving: RoHS, Veiligheid: EN 60825-1, Certificering: CE, FCC. Breedte: 57 mm,

Diepte: 12 mm, Hoogte: 13,7 mm. Aantal per verpakking: 1 stuk(s)



Prestatie		Energie	
SFP transceiver type *	Vezel-optiek	Stroom (max.)	0,3 A
Maximale overdrachtssnelheid van gegevens *	1250 Mbit/s	Certificaten	
Soort aansluiting *	SFP	Certificaten van naleving	RoHS
Single-mode glasvezelkabel (SMF) ondersteund	✗	Veiligheid	EN 60825-1
Multi-mode glasvezelkabel (MMF) ondersteund	✓	Certificering	CE, FCC
Kenmerken		Eisen aan de omgeving	
Vezel-optische connector	LC	Bedrijfstemperatuur (T-T)	0 - 70 °C
Vezelkabel diameters ondersteund	50/125,62.5/125 µm	Temperatuur bij opslag	-40 - 85 °C
Maximaal bereik	550 m	Relatieve vochtigheid in bedrijf (V-V)	5 - 95 procent
Golflengte	850 nm	Gewicht en omvang	
Tx vermogen (min)	-9,5 dBmW	Breedte	57 mm
Tx vermogen (max)	-3 dBmW	Diepte	12 mm
Netwerkstandaard	IEEE 802.3z	Hoogte	13,7 mm
Duplex systeem	Volledig	Gewicht	20 g
Fibre channel-poorten	1	Inhoud van de verpakking	
Energie		Aantal per verpakking	1 stuk(s)
Ingangsspanning	3.3 V	Verpakking	
Maximaal voltage	6 V	Breedte verpakking	106 mm
		Diepte verpakking	20 mm
		Hoogte verpakking	65 mm
		Gewicht verpakking	35 g
		Logistieke gegevens	
		Code geharmoniseerd systeem (HS) 85369010	



4015867154663



8787420086044

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.